

TU-1510AE

AM/FM Stereo Tuner

100th
Anniversary
since 1910

DENON

The TU-1510AE is an AM/FM stereo tuner featuring highly sensitive reception performance and detailed, clear sound even in crowded urban areas.



RDS RadioTEXT

Features

- **Design matching Integrated Amplifier for the new 10AE series**

The TU-1510AE sports an external design that harmonizes well as a system upgrade for Denon's latest AE series of Hi-Fi audio components. The TU-1510AE comes in a choice of two colours, premium silver and black, and together with its aluminium panel of rich texture this tuner achieves a tasteful ambience that enhances the total design balance of the AE Hi-Fi audio system.

- **Rotary knob, for easy tuning and preset operation**

The TU-1510AE's rotary knob makes tuning and operating presets a breeze. Simply turn it to the left or right to access the station you want.

- **Easy-to-read dot matrix and 2-line FL display**

The TU-1510AE features a large dot matrix display panel with vastly improved visual recognition characteristics. Alphanumerics are displayed more smoothly, allowing users to read the information more quickly.

- **Low-impedance output circuit for high quality sound**

The output circuit in the TU-1510AE has an impedance of less than 300 ohms to enable greater density in signal transmission to the amp for superior attenuation characteristics in the high-frequency range and a highly transparent sound quality.

- **Easy-to-use, dedicated remote control unit**

The TU-1510AE comes with its own remote controller that lets you conveniently perform operations such as adjusting reception frequencies up or down, flicking through preset channels, and switching bands.

- **Preset memory for a total of 100 FM/AM stations, and Auto preset memory for automatically scanning and storing stations that can be received**

- **Up to 8 alphanumerics can be stored for displaying station call letters, nick-names, or other information.**

Main Specifications

FM section

Tuning frequency	87.50 MHz - 108.00 MHz
Usable sensitivity	1.0 μ V (11.2dB η) / 1.2 μ V (IHF)
Signal-to-noise ratio	Mono: 77 dB (IHF), 73 dB (DIN) Stereo: 72 dB (IHF), 68 dB (DIN)
Total Harmonic Distortion	Mono: 0.15 % Stereo: 0.3 %
Frequency response	20 Hz - 15 kHz (-1.0, +0.5dB)
Stereo separation 1 kHz	43 dB

AM section

Tuning frequency range	522 kHz - 1611 kHz
Usable sensitivity	18 μ V
Signal-to-noise ratio	53 dB

General

Power supply	AC 230 V, 50 Hz
Power consumption	10 W
Dimensions W x H x D	434 x 73 x 286 mm
Weight	3.6 kg

Ports

Out	RCA analog	x 1
Others	FM tuner antenna	x 1
	AM tuner antenna	x 1
	Inlet type AC-Code	yes



*Black version is also available.

*Design and specifications are subject to change without notice.